

TECHNICAL DATASHEET

TOMLED-PRS WHITE Ø60CM 60W

03-07-2020



NO IMAGE
AVAILABLE

RLT/TomLED – PRs/PENDANT/Ø60 H8CM/WHT-B/OP-D/65K

NOTES

Turkey
Discover
the potential

General Informations

Stock Code	2423570
HSC/GTIP Code	9405.10.98.50.00

Lighting Characteristics

Luminous Flux	8280 lumen
Time for 60% of Lumen	<0.5 seconds
Light Beam Angle	160°
Flicker	No
LED Type	SMD

Electrical Characteristics

Current Type	AC
Operation Voltage	220-240 Volt
Operation Frequency	50/60 Hertz
Power	60 Watt
Power Factor	>0.9
Luminous Efficiency	138 lumen/Watt
Energy Savings	0,87
Dimmable	No
Electrical Protection Class	Class I

Mechanical Parameters

IP Protection Class	IP20
Switch On/Off Cycle	30000
Lifetime	50000 hours
Body Material	Aluminum
Body Colour	White
Diffuser Material	PC Opal Diffuser with High Permeability
Product Height	80 millimeter
Product Width	Ø600 millimeter
Product Depth	80 millimeter
Ambient Temperature (Ta)	-20°C<Ta<40°C

Electrical Component Specifications

Component Fitting Type	Internal Driver
Driver Properties	Isolated IC
Driver Input Voltage	220-240 Volt

IMPORTANT NOTES: VITO reserves the right to change/remove models or specifications partially/completely without any notice. Information, models and photographs of the products in this technical datasheet can not be used, reproduced or republished without permission. However, some parts can be quoted by giving reference and/or chapter number belonging to technical datasheet. Most of the items in the datasheet have been designed by our company within indicated technical specifications inside. Our company is not responsible for errors caused by wrong installation and operating against rules according to qualifications specified in the product details. Photographs printed in this datasheet may not reflect the actual color of the product depending on printing conditions. In the same context, typographical errors may possibly be found in the texts.