

<b>CCT (KELVIN)</b>	3000K (WARM WHITE)	<b>POWER (W)</b>	50.0	<b>LUMINUS EFFICIENCY</b>	100	<b>LIGHT BEAM ANGLE</b>	120°
<b>CRI</b>	80	<b>POWER FACTOR</b>	0.9	<b>FLICKER</b>	No	<b>IP PROTECTION CLASS</b>	IP20
<b>SWITCH ON/OFF</b>	30000	<b>LIFETIME (H)</b>	50000	<b>DIMMABLE</b>	No	<b>OPERATION VOLTAGE (V)</b>	220V- 50/60Hz
<b>ENERGY SAVING (%)</b>	88%	<b>ELECTRICAL EFFICIENCY INDEX (EEI)</b>	E	<b>ELECTRICAL PROTECTION</b>	Class I	<b>BODY MATERIAL</b>	Aluminum
<b>DIFFUSER MATERIAL</b>	Polycarbonate Opal Diffuser with High Permeability	<b>BODY COLOR</b>	WHITE	<b>DIMENSIONS (mm)</b>	1490x53x83mm	<b>TEMPERATURE (Ta)</b>	-20°C Ta 40°C
<b>GUARANTEE PERIOD (y)</b>		5	<b>LUMINUS FLUX (Lm)</b>	5000	<b>PCS PER BOX</b>	1	